



keepower® X8

Intelligent battery care

The **Keepower "x8"** multiple charger station enables you to charge up to 8 different batteries simultaneously. The multiple charger station can be mixed with either 1A/4A 12V or 0,8A 12V battery chargers and allows you to charge and maintain different sized batteries. All lead-acid batteries for motorcycles, cars, etc. can be charged and maintained (MF, GEL, VRLA, AGM, etc.).

GB

Keepower "x8" lader-station gør dig i stand til at oplade helt op til 8 forskellige batterier ad gangen. Lader-stationen kan kombineres med forskellige ladere, enten 1A/4A 12V eller 0,8A 12V batteri-opladere og gør dig i stand til også at vedligeholde forskellige størrelser af batterier. Alle batterier til motorcykler, biler osv., kan oplades og vedligeholdes (MF, GEL, VRLA, AGM, osv.).

DK

The **Keepower "x8"** multiple charger station enables you to charge up to 8 different batteries simultaneously. The multiple charger station can be mixed with either 1A/4A 12V or 0,8A 12V battery chargers and allows you to charge and maintain different sized batteries. All lead-acid batteries for motorcycles, cars, etc. can be charged and maintained (MF, GEL, VRLA, AGM, etc.).

PL

| TECHNICAL SPECIFICATIONS | MICRO | SMALL | CE GB |
|-------------------------------|-------------------------------|-------------------------------|-------|
| Nominal battery voltage | 12V | 12V | |
| Charge current | 0,8A | 1A/4A | |
| Battery size | 1,2Ah to 32Ah | 3Ah to 80Ah | |
| Max. total outputpower | 16W | 60W | |
| Input voltage (Mains voltage) | 230Vrms ± 10% 50Hz ± 3Hz | 230Vrms ± 10% 50Hz ± 3Hz | |
| Ripple voltage* | <100mVpp | <100mVpp | |
| Current voltage* | 3% | 3% | |
| Protection classification | IP65 | IP65 | |
| Dimensions (LxWxH) | 146 x 89 x 52 mm. | 146 x 89 x 52 mm. | |
| Weight | 0,490kg | 0,490kg | |
| Length main cabel | 2 m. | 2 m. | |
| Charging Cable | 0,75 mm ² / 2,5 m. | 0,75 mm ² / 2,5 m. | |

* Charging old battery with 40% capacity left

| TECHNICAL SPECIFICATIONS | MICRO | SMALL | CE GB |
|-------------------------------|-------------------------------|-------------------------------|-------|
| Nominal battery voltage | 12V | 12V | |
| Charge current | 0,8A | 1A/4A | |
| Battery size | 1,2Ah to 32Ah | 3Ah to 80Ah | |
| Max. total outputpower | 16W | 60W | |
| Input voltage (Mains voltage) | 230Vrms ± 10% 50Hz ± 3Hz | 230Vrms ± 10% 50Hz ± 3Hz | |
| Ripple voltage* | <100mVpp | <100mVpp | |
| Current voltage* | 3% | 3% | |
| Protection classification | IP65 | IP65 | |
| Dimensions (LxWxH) | 146 x 89 x 52 mm. | 146 x 89 x 52 mm. | |
| Weight | 0,490kg | 0,490kg | |
| Length main cabel | 2 m. | 2 m. | |
| Charging Cable | 0,75 mm ² / 2,5 m. | 0,75 mm ² / 2,5 m. | |

* Charging old battery with 40% capacity left

| TECHNICAL SPECIFICATIONS | MICRO | SMALL | CE GB |
|-------------------------------|-------------------------------|-------------------------------|-------|
| Nominal battery voltage | 12V | 12V | |
| Charge current | 0,8A | 1A/4A | |
| Battery size | 1,2Ah to 32Ah | 3Ah to 80Ah | |
| Max. total outputpower | 16W | 60W | |
| Input voltage (Mains voltage) | 230Vrms ± 10% 50Hz ± 3Hz | 230Vrms ± 10% 50Hz ± 3Hz | |
| Ripple voltage* | <100mVpp | <100mVpp | |
| Current voltage* | 3% | 3% | |
| Protection classification | IP65 | IP65 | |
| Dimensions (LxWxH) | 146 x 89 x 52 mm. | 146 x 89 x 52 mm. | |
| Weight | 0,490kg | 0,490kg | |
| Length main cabel | 2 m. | 2 m. | |
| Charging Cable | 0,75 mm ² / 2,5 m. | 0,75 mm ² / 2,5 m. | |

* Charging old battery with 40% capacity left

